



FOUR POST SIDE-BY-SIDE COMPARISON



SPECIFICATIONS	PP8S	PP8PL	PP9PL	PRO 14
Capacity	8,000 lbs.	8,000 lbs.	9,000 lbs.	14,000 lbs.
Lifting Height	72"	86"	85"	73-3/4"
Overall Length w/Approach Ramps	208"	222-1/4"	221"	246-3/4"
Overall width (with motor)	115-1/2"	115"	131"	137-1/4"
Overall width (without motor)	103-1/2"	103-1/2"	121"	125-1/4"
Overall Length without Approach Ramps	176"	190"	197"	210"
Approach Ramps	37"	36-3/4"	31"	37"
Runway Width	18-1/2"	18-1/2"	20"	20"
Runway Length	166"	180"	188"	195-1/4"
Runway Thickness	4-1/2"	5"	5"	7"
Drive through width (Outside of tire to outside of tire)	80-1/2"	80-1/2"	79-1/2"	83"
Height of Columns	83"	95-3/4"	97"	88-3/4"
Clearance Between Columns	94"	94"	109 1/2"	114-1/4"
Clearance Between Runways	37"	37-3/4"	39-1/2"	43"
Outside Runway to Outside Runway	75"	74-3/4"	79-1/2"	83"
Clearance Under Runways	68"	81"	80"	66-3/4"
Motor	110 Volt, 1HP	110 Volt, 1HP	110 Volt, 1HP	208/230, 2 HP
Shipping Weight	1,820 lbs.	1,920 lbs.	2,350 lbs.	3,050 lbs.

Specifications subject to change without notice or liability.