

Direct Lift Four Post Side-by-Side Comparison



| SPECIFICATIONS | PP8S | PP8 PLUS | PP9 PLUS |
|---|---------------|---------------|---------------|
| Capacity | 8,000 lbs. | 8,000 lbs. | 9,000 lbs. |
| Lifting Height | 72" | 86" | 85" |
| Overall Length w/Approach Ramps | 207.5" | 207.5" | 218.5" |
| Overall width (with motor) | 115" | 115" | 133" |
| Overall width (without motor) | 103.5" | 103.5" | 121" |
| Overall Length without Approach Ramps | 176" | 176" | 197" |
| Approach Ramps | 37" | 37" | 31" |
| Runway Width | 19" | 19" | 21.5" |
| Runway Length | 165.5" | 165.5" | 188" |
| Runway Thickness | 4.5" | 5" | 5" |
| Drive through width (Outside of tire to outside of tire) | 80.5" | 80.5" | 97.5" |
| Height of Columns | 83" | 95.75" | 97" |
| Clearance Between Columns | 94" | 94" | 109.5" |
| Clearance Between Runways | 37" | 37" | 39.25" |
| Outside Runway to Outside Runway | 75" | 75" | 79.25" |
| Clearance Under Runways | 68" | 81" | 80" |
| Power Unit | 110 Volt, 1HP | 110 Volt, 1HP | 110 Volt, 1HP |
| Shipping Weight | 1,720 lbs. | 1,739 lbs. | 2,300 lbs. |